

## DuPont™ 18258S™ Solventborne Cleaner – High Temperature

### Type

DuPont™ 18258S™ is a multi-use cleaning solvent.

### Description

DuPont 18258S™ is a solvent blend suitable for cleaning substrates and equipment used in polyurethane and epoxy coating operations. This is formulated to be effective in hot, humid conditions.

### Recommended Uses

DuPont 18258S™ is recommended for a wide range of surface preparation and final paint cleaning applications. Due to the potential for static generation, it is not recommended for use directly on or fiberglass or gelcoat.

### General Information for Use


#### Components

DuPont 18258S™ Solventborne Cleaner



#### Mix Ratio

Ready to use.



### Factory-Packaged Cleaner

Color	Clear
Closed Cup Flash Point	Below 70°F (21°C)
Shelf Life	3 years (Unopened at 50° – 110°F)
Gallon Weight	6.5 lbs/gal

### Physical Properties

VOC	<i>Less Exempt (LE)</i>	<i>As Packaged (AP)</i>
DuPont 18258S™ Solvent Borne Cleaner	6.5 lbs/gal	6.5 lbs/gal

### **Safety and Handling**

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Do not allow material to enter drains or waterways.

E-R 4686/K-17179  
Revised 5/2007